## Docuware Cover Sheet DWR

Cabinet (circle one): DWR RRCA ARCA GMD	
File Name State Programs	(from index)
Sub File Name ASR	(from index)
Sub-Sub File Name Wichita	,
Year (calendar) 2010	
End Year	
Privileged Yes - Circle if true	
Comments/Keywords Accounting and Annual report 2009 Review	A <b>)</b>
After scanning:	
File hard copy CE Desk / CE Cabinet / Laterals	
Send to Archives	
Send to Field Office	
Recycle	
File only:	
File hard copy CE Desk / CE Cabinet / Laterals	

LARRY JACOB, PRESIDENT DAVID STROBERG, VICE PRESIDENT FRED SEILER, SECRETARY DON KOCI, TREASURER TIM BOESE, MANAGER THOMAS A. ADRIAN, ATTORNEY



DIRECTORS:
CHRIS CARRIER
DENNIS GRUENBACHER
VIN KISSICK
MIKE MCGINN
BOB SEILER

### equus beds groundwater management district NO. 2

313 SPRUCE STREET · HALSTEAD, KANSAS 67056-1925 · PHONE (316) 835-2224 · FAX (316) 835-2225 · equusbeds@gmd2.org · www.gmd2.org

September 23, 2010

David Barfield, Chief Engineer Division of Water Resources Kansas Department of Agriculture 109 S.W. 9<sup>th</sup> Street, Second Floor Topeka, Kansas 66612-1283

Re: Aquifer Storage and Recovery Project 2009 Accounting (& Annual) Report

Dear Mr. Barfield:

The City of Wichita Aquifer Storage and Recovery (ASR) Project 2009 Accounting Report was reviewed by the Equus Beds Groundwater Management District Board of Directors at the September 15, 2010, meeting. The 2009 Accounting Report also included the elements required in the Annual Report specified in K.A.R. 5-22-10(a), effectively combining the reports into one report. A copy of the District's Fact and Information Review Sheet is enclosed for your information.

Upon review of the report, the District Board of Directors determined that the report satisfies the requirement set forth in the initial (and as later modified) order for the ASR project and satisfies the conditions of the Aquifer Storage and Recovery System: Data Reporting Requirements Regulation K.A.R. 5-22-10(a), subject to providing the information concerning the key groundwater quality parameters as required by K.A.R. 5-22-10(a)(4)(B), once the data is made available by the United States Geological Survey (USGS). Additionally, the City's consultant advised that the quarterly water-level change maps not included in the report would be provided once the maps are completed by USGS.

The Board of Directors recommends that subsequent ASR Project Accounting (& Annual) Reports include:

- Water quality information presented in an improved manner, utilizing elements such as tables and graphs.
- Index groundwater levels are presented graphically (hydrographs) and geographically (water-level change maps).

Please contact the District should you have any questions regarding the review or recommendations.

Sincerely,

EQUUS BEDS GROUNDWATER MANAGEMENT DISTRICT NO. 2

Tim Boese Manager

TDB/db

**Enclosure** 

pc: Debra Ary, City of Wichita

Paul McCormick, Burns and McDonnell

Jeff Lanterman, Division of Water Resources, Stafford

WATER RESOURCES
AECEIVED

SEP 27 2010

KS DEPT OF AGRICULTURE



H:\MSOFFICE\LETTERS\BANK\\$2009 Accounting&Annual\_Report\_RC.doc

# Equus Beds Groundwater Management District Board of Directors Fact and Information Review Sheet

City of Wichita, 2009 Aquifer Storage and Recovery Project 2009 Accounting & Annual Report Summary

By

Daniel Clement and Tim Boese, GMD2 September 14, 2010

#### **Background:**

Construction of phase I of the ASR project was substantially completed on September 13, 2006 and phase II is currently under construction. During 2009 the City operated three diversion wells, a surface water treatment and intake plant, four recharge wells, and Recharge Basin No. 2. Per DWR Chief Engineer's orders, recharge credit accounting must use an adequate groundwater model that addresses the many natural and artificial sources of groundwater gains and losses within the storage area. The ASR Phase I project operated for a third full year in 2009.

#### Source Water & Aquifer Storage:

**Type -** Recharge water was taken directly from the Little Arkansas River using surface water and groundwater from the three diversion wells located along the river bank.

**Quantity Available -** Based on stream gauges stream flow exceeded the minimum limits for diversion and recharge for a total of 280 days in 2009

Quantity Diverted – Diversions totaled 556.03 acre-feet with metered recharge at 521.78 acre feet as shown in the tables below. Well maintenance consumed 3.74 acre-feet, while system operations consumed 34.25 acre-feet. Surface water that passes through plant during startup is not recharged due to high turbidity. This water was diverted to a drainage ditch and was not metered. Water used for flushing surface water pipeline and for system deactivation is also diverted to a drainage ditch.

**Techniques Used** – During 2009, water was recharged via four recharge recovery wells (RRW) and recharge basin 2 (RB2).

WATER RESOURCES

SEP 27 2010

From Table 2.1 2009 Metered Diversion and Recharge Volumes

Diversions:	Gallons	Acre-Feet
Surface Intake	22,745,792	69.81
DW1	60,258,960	184.94
DW2	36,911,313	113.28
DW3	61,256,432	188.00
		Total: 566.03

Recharged (metered):	Gallons	Acre-Feet	
RB2	52,498,208	161.12	
RRW1	16,182,600	49.67	
RRW2	28,374,240	87.08	
RRW3	27,865,840	85.52	
RW1	45,091,616	138.39	
And a state of the		Total: 521.78	

Well Maintenance Pumping:	Gallons	Acre-Feet		
RRW1	175,668	0.54		
RRW2	360,811	1.11		
RRW3	332,874	1.02		
RW1	348,132	1.07		
		<b>Total:</b> 3.74		

WATER RESOURCES
PEGEIVED
SEP 27 2010

Physical and Chemical properties of Source Water – Water captured from bank storage wells was not treated, but recharge quality remained good. All surface water diverted from the Little Arkansas River was treated and all water recharged met MCL established for drinking water. Additional filtration is implemented at RB2 to remove biological constituents from surface water. Data was included in the report inside Appendix C.

**Recharge Credits Withdrawn** - There has been no recovery of stored water to date.

#### **Hydrologic Conditions:**

**Quarterly index water levels** - Water level measurements for the ASR index wells were obtained via GMD2 and were supplied in the report in Appendix C. However, only the water-level change map for the 1<sup>st</sup> quarter of 2009 was available.

**Key groundwater quality parameters** – The USGS collects samples from the Index Wells on an annual basis. The data was not available at the time of the report thus this information was not included. This data will be provided as it becomes available.

**Monthly and annual precipitation data** – The monthly annual precipitation data was provided by GMD2. The McPherson County weather station served as representative data for the area. The monthly data was included as Appendix G in the report.

**Withdrawals from Non-domestic wells -** DWR provides the city with a spreadsheet showing the pumping from all non-domestic wells for use in the annual accounting model. According to the 2009 data furnished by DWR, 167,657.93 acre-feet was pumped from the Basin Storage Area. This data was included as Appendix H in the report.

Annual stream flow, including baseflow and above baseflow stages – The annual stream flow data for the Little Arkansas River was obtained from the USGS and is included as Appendix I.

SEP 27 2010

**Summary of conjunctive use amounts -** Conjunctive use amounts are totaled when the City uses more than its base water rights of 53,000 acre-feet from Cheney during wet years. This did not happen in 2009, so the conjunctive use amount is 0.0 acre-feet.

Water supply and demand forecast for next three years – The City's current water supplies are anticipated to meet the projected demands, and no ASR credits are anticipated to be used in the next three years.

Year	Gallons	
2011	21,715,000,000	
2012	21,900,000,000	
2013	22,630,000,000	

#### Other Supporting Documentation:

**Groundwater Modeling** – DWR requires a groundwater-based accounting system to track movement of recharge credits as a condition for approval of permits required to capture, store and recover water for beneficial use by the City. Several models are currently being utilized to track the groundwater movement of the ASR project recharge credits. Models included dynamic and acceptable calibrated parameters to produce more accurate results. Models account for precipitation, stream flow, groundwater pumping, natural vs artificial recharge, individual cell inflow and outflow, evaporation and transpiration, and target accurate stream infiltration rates.

For the accounting model, a total of 38 hydrostratigraphic units were established and numbered to represent the 38 ASR index cell areas. Several index cells were extended eastward in the model to include the river. The map below was taken from the report (Figure 4.2). Hydrologic data for each index cell was included in Appendix A and B. Calculated model data indicates that the barrier to the Burrton Salt Water Plume is beginning to form.



Figure 4.2 - A map of the Hydrostratigraphic Units used in the ASR area.




Table 4.3 2009 Recharge Credit Summary (Acre-Feet)

Jane 1			(27018-1				SOLOGIC CONTRACTOR OF THE PARTY
				Net	Net		
1				Recharge	Recharge	Net	
	Previous			Credit	Credit	Recharge	_ ,
1	Recharge	2009	2009	Underflow	Underflow	Credit	Current
	Credit	Metered	Metered	Entering	Leaving	Loss to	Recharge
Index Call	(2006-2008)	Recharge	Recovery	Index Cell	Index Cell	River	Credit
1	7373					CIES	RESE
2	197.0	49.7	1.5	82.8	124.3		203.7
3	19.3			187.7	35.5	0.0	171.5
4	18 N 100.18						
5	324.3	85.5	6.0	48.8	186.1		266.6
6	63,3		,	172.5	183.7	4122	52.2
7	22.1			91.7	16.6	73.2	97.2
B				Dem.	E.FR.	9523	
. 9	227.0	138.4	2.9	56.3	150.1		268.6
10	63.8			102.9	106.0		60.7
11	26.0			60.0	45.7	9.0	31.3
12	5.2	į		15.5	3.1	11.4	6.2
13				REST	esse	5000	
14	296.9	161.1	0.0	-23.8	102.8	AFF	331.4
15	43.8			57.9	49.0		52.7
16	21.6			38.6	28.7	5 E-10	31.4
17	5.7		•	19.7	9.8	5.7	9.9
18	ESEE	***************************************					
19	24.8			- <b>2</b> .8	-19.1		41.0
20	18.4			17.7	8.0		28.1
21	12.0			22.2	13.8	E377	20.3
22	4,1			11.8	7.7	6312	8.1
23	1.1		i	4,4	1.6	1.9	2.0
24				6252	1.0	1-4	
25	8.5			6.2	5.9		8.9
26	1.2			10.3	8.8		2.7
27	5,8			8.4	4.7	EIES	9.4
28	2.4			4.9	2.5		4.8
20 29	0.7			2.3	0.9	0.3	1.7
30				4.2	2.7	V.Q.	2.0
	0.5			3.0	1.9		2.8
31	1.à						1.7
32	0.8			1.7	0.9	2214	Total programme and the second
33	0.3			0,9	0.4		0.8
34	0.0		*	0.3	0.0	0.2	0,1
35	0.5	***************************************	<del>,</del>	0.6	0.2	<u>0.1</u>	0.8
36	0.2			0,4	0.2		0.4
37	0.1			0.2	0.1		0.2
38	0.0			0.1	0.0	0.0	0.0
Total	1399.06	434.7	10.3	1007.2	1082.6	101.8	1719.4

Total water recharged to the basin 2006 through 2009 is 2529.10 acre-feet. Total recharge credit established through 2009 is 1719.4 acre-feet, which is approximately 68% of the total water recharged.

WATER RESOURCES DECEMEN

SEP 27 2010

#### **Staff Comments:**

- For 2009, the Accounting and Annual Reports have been combined, as many reporting requirements are common to both reports.
- The 2009 Accounting & Annual Report meets the requirements set forth in the initial and (and as later modified) order for the ASR project and the Aquifer Storage and Recovery System: Data Reporting Requirements Regulation K.A.R. 5-22-10(a), pending a list of the key groundwater quality parameters as required by K.A.R. 5-22-10(a)(4)(B).
- Water quality information should be presented in an improved manner such as tables and graphs.
- Index water-levels should be presented graphically (hydrographs) and geographically (water-level change maps)